

Part Prefix Table ①

	Orifice		MOPD (psi)	C _v		① Primary Prefix	
	Body	Stop		Body	Stop	Grommet Housing	Unfilled Conduit Housing
3-WAY	1/32	3/64	100	0.018	0.040	BL3111	BL3121
	1/16	1/16	50	0.070	0.070	BL3113	BL3123
2-WAY	1/16	—	240	0.065	—	BL2011	BL2021
	5/64	—	180	0.09	—	BL2012	BL2022
	3/32	—	150	0.155	—	BL2013	BL2023
	7/64	—	120	0.2	—	BL2014	BL2024
	1/8	—	90	0.24	—	BL2015	BL2025
	5/32	—	60	0.3	—	BL2016	BL2026
	3/16	—	30	0.43	—	BL2017	BL2027

② Coil Construction

- 1 = Encapsulated Coil, Class-B (130°C), Lead Wires 18" Long, #20 AWG
- 2 = Encapsulated Coil, Class-F (155°C), Lead Wires 18" Long, #20 AWG

③ Body Material

- BB = Brass
- SB1 = 303 Stainless Steel
- SB5 = 316 Stainless Steel

④ Plunger Seal Material

- H = Hydrin®
- V = Viton®
- PF = Perfluoroelastomer

⑤ O-Ring Material

- NBO = Nitrile®
- VO = Viton®
- PFO = Perfluoroelastomer

⑥ Body Port Configuration

- LC = 1/8" NPT female ports
- LD = 1/4" NPT female ports
- MM3 = Manifold-Mount (5/16" thread stud)

⑦ Exhaust Port

- (blank) = #10-32 female thread*
- AB = 1/8" Brass Barb Fitting
- AD = 1/8" NPT Brass Adapter

⑧ Voltage

- C202 = 6 VDC, 7 Watts Latching, 5 Watts Unlatching
- C203 = 12 VDC, 9 Watts Latching, 7 Watts Unlatching
- C204 = 24 VDC, 9 Watts Latching, 7 Watts Unlatching
- C202D = 6 VDC, 7 Watts Latching, 5 Watts Unlatching with internal diodes
- C203D = 12 VDC, 9 Watts Latching, 7 Watts Unlatching with internal diodes
- C204D = 24 VDC, 9 Watts Latching, 7 Watts Unlatching with internal diodes

⑨ Wire Color Codes

- WGR-N = White common (+), Green latch (-), Red Unlatch (-)
- BRG-P = Black common (-), Red latch (+), Green Unlatch (+)
- BGR-N = Black common (+), Green latch (-), Red Unlatch (-)

* Standard selection; will be used unless otherwise specified. Standard selections are not referenced in final part number.