

- > Port size: DN 8 ... 50, 1/4" ... 2" (ISO G/NPT)
- > Compact build piston valve
- > Functional design
- > High flow rate
- > Damped operation via cone
- > Piston guided in PTFE rings
- > Long lifetime
- > Solenoid interchangeable without tools (*Click-on®*)



Technical features

Medium:

Neutral gases and liquids

Switching function:

Normally closed

Operation:

Indirectly solenoid actuated

Mounting:

Optional, preferably solenoid vertical on top

Flow direction:

Determined

Port size:

G1/4, G3/8, G1/2, G3/4, G1, G1 1/4, G1 1/2, G2
 1/4 NPT, 3/8 NPT, 1/2 NPT, 3/4 NPT, 1 NPT, 1 1/4 NPT, 1 1/2 NPT, 2 NPT

Operating pressure:

0,5 ... 40 bar (7 ... 580 psi)

Fluid temperature:

-20° ... +90°C (-4° ... +194°F)

Ambient temperature:

-20° ... +50°C (-4° ... +122°F)

Materials:


Body: Brass (CW617N)

Seat seal: NBR

Internal parts: Stainless steel, Brass, PTFE/Carbon

For contaminated fluids insertion of a strainer is recommended.

Technical data - standard models

Symbol	Port size	Orifice (mm)	Flow kv value *1) (m³/h)	Operating pressure *2) (bar)	Weight (kg)	Model Solenoid in d.c./a.c.
	G1/4	8	2,2	0,5 ... 40	0,83	8536000.9151.xxxxx
	1/4 NPT	8	2,2	0,5 ... 40	0,83	8537000.9151.xxxxx
	G3/8	10	3,4	0,5 ... 40	0,82	8536100.9151.xxxxx
	3/8 NPT	10	3,4	0,5 ... 40	0,82	8537100.9151.xxxxx
	G1/2	12	4,4	0,5 ... 40	0,85	8536200.9151.xxxxx
	1/2 NPT	12	4,4	0,5 ... 40	0,85	8537200.9151.xxxxx
	G3/4	20	7	0,5 ... 40	1,25	8536300.9151.xxxxx
	3/4 NPT	20	7	0,5 ... 40	1,25	8537300.9151.xxxxx
	G1	25	10,5	0,5 ... 40	1,7	8536400.9151.xxxxx
	1 NPT	25	10,5	0,5 ... 40	1,7	8537400.9151.xxxxx
	G1 1/4	32	25	0,5 ... 40	4,1	8536500.9151.xxxxx
	1 1/4 NPT	32	25	0,5 ... 40	4,1	8537500.9151.xxxxx
	G1 1/2	40	27	0,5 ... 40	3,85	8536600.9151.xxxxx
	1 1/2 NPT	40	27	0,5 ... 40	3,85	8537600.9151.xxxxx
	G2	50	43	0,5 ... 40	5,6	8536700.9151.xxxxx
	2 NPT	50	43	0,5 ... 40	5,6	8537700.9151.xxxxx

xxxxx Please insert voltage and frequency codes

*1) Cv-value (US) ≈ kv value x 1,2

*2) For gases and liquid fluids up to 25 mm²/s (cSt)

Option selector

853*****.9151.*****

Thread form	Substitute
ISO G	6
NPT	7
Port size	Substitute
1/4"	0
3/8"	1
1/2"	2
3/4"	3
1"	4
1 1/4"	5
1 1/2"	6
2"	7
Valve options	Substitute
Normally open (NO), up to DN 25: Operating pressure 0,5 ... 35 bar from DN 32: Operating pressure 0,5 ... 25 bar	01
Manual override	02
Seat seal FPM, Fluid temperature -10 ... +110°C	03
Seat seal PTFE, Fluid temperature -10 ... +110°C, Operating pressure 1 ... 25 bar	06
Seat seal EPDM, for hot water, Fluid temperature -20 ... +110°C	14
Version for drinking water on request	

Frequency	Substitute
See table frequency codes	xx
Voltage	Substitute
See Voltage codes	xxx

Standard solenoid systems

Voltage and Frequency Solenoid 9151 *1)					
Code	Code	Voltage	Frequency	Power consumption	
Voltage	Frequency			Inrush	Holding
024	00	24 V d.c.	-	18 W	18 W
024	50	24 V a.c.	50 Hz	45 VA	35 VA
110	50	110 V a.c.	50 Hz	45 VA	35 VA
120	60	120 V a.c.	60 Hz	45 VA	35 VA
230	50	230 V a.c.	50 Hz	45 VA	35 VA

*1)  US coil only

Further versions on request!

Electrical details for all solenoid systems

Design	DIN VDE 0580
Voltage range	±10%
Duty cycle	100% ED
Protection class	EN 60529 IP65
Socket	Form A acc. to DIN EN 175301-803 (included)

According to DIN VDE 0580 at a solenoid temperature of +20°C.
At operating state temperature the input power of a coil decreases by up to ca. 30% due to physical reasons.




Additional solenoid systems

ATEX category	Protection class	Solenoid	Standard voltages
I13G I13D	Ex II 3G Ex nA IIB T4 Gc Ex II 3D Ex tc IIIB T130°C Dc IP65	9176	24 V d.c., 110 V a.c., 230 V a.c.
I12GD	Ex me II T4 T110°C	9186	24 V d.c., 110 V a.c., 230 V a.c.
I12GD	Ex dmb IIC T4/T5 Ex tD A21 IP66 T130°C up to DN 25: Operating pressure 0,5 ... 16 bar from DN 32: Operating pressure 0,5 ... 10 bar	468x	24 V d.c., 110 V a.c., 230 V a.c.

Attention!

The conditions imposed on the Ex approvals lead to reduction of the permissible standard temperature ranges in the cases of explosion protected solenoids.

Section View
G1/4 ... 2
1/4 ... 2 NPT




No.	Description
101	Valve body
102	Valve cover
*103	Valve plate
104	Allen head screw
*105	Pressure spring
*106	Gasket
*107	O-ring / gasket
400	Solenoid
701	Core tube
*702	O-ring
*704	Pressure spring
*705	Plunger
706	Spring clip
*707	O-ring
1400	Socket (included)

* These individual parts form a complete wearing unit.
 When ordering spare parts please state Model No. and Series No.

Dimensions

G1/4 ... 2
1/4 ... 2 NPT

Dimensions in mm
Projection/First angle



- 1 Solenoid rotatable 360°
- 2 Socket turnable 4 x 90°
(Socket included)

Port size R	ø B	H	H1	L	T	Model
G1/4	44	105	93,5	60	12	8536000.9151.xxxxx
1/4 NPT	44	105	93,5	60	12	8537000.9151.xxxxx
G3/8	44	105	93,5	60	12	8536100.9151.xxxxx
3/8 NPT	44	105	93,5	60	12	8537100.9151.xxxxx
G1/2	44	107,5	102,5	67	14	8536200.9151.xxxxx
1/2 NPT	44	107,5	102,5	67	14	8537200.9151.xxxxx
G3/4	50	119	102,5	80	16	8536300.9151.xxxxx
3/4 NPT	50	119	102,5	80	16	8537300.9151.xxxxx
G1	62	131,5	110,5	95	18	8536400.9151.xxxxx
1 NPT	62	131,5	110,5	95	18	8537400.9151.xxxxx
G 1 1/4	92	166	137	132	20	8536500.9151.xxxxx
1 1/4 NPT	92	166	137	132	20	8537500.9151.xxxxx
G1 1/2	92	166	137	132	22	8536600.9151.xxxxx
1 1/2 NPT	92	166	137	132	22	8537600.9151.xxxxx
G2	109	186	151,5	160	24	8536700.9151.xxxxx
2 NPT	109	186	151,5	160	24	8537700.9151.xxxxx

Note to Pressure Equipment Directive (PED):

The valves of this series, including the connection size DN 25 (G 1), are according to Art. 3 § 3 of the Pressure Equipment Directive (PED) 97/23/EG. This means interpretation and production are in accordance to engineers practice wellknown in the member countries. The CE-sign at the valve refers not to the PED. Thus the declaration of conformity is not longer applicable for this directive.

For valves > DN 25 (G 1) Art. 3 § (1) No.1.4 applies:

The basic requirements of the Enclosure I of the PED must be fulfilled. The CE-sign at the valve includes the PED. A certificate of conformity of this

directive will be available on request.

Note to Electromagnetic Compatibility Guideline (EEC):

The valves shall be provided with an electrical circuit which ensures the limits of the harmonised standards EN 61000-6-3 and EN 61000-6-1 are observed, and hence the requirements of the Electromagnetic Compatibility Guideline (2004/108/EG) satisfied.